



MINOR COLLECTOR

NOTES:

1. A.C. PAVEMENT TO BE 1/2" MAXIMUM ABOVE LIP OF GUTTER AFTER COMPACTION. PAVEMENT SHALL BE FLUSH WITH LIP AT SIDEWALK RAMPS.
2. THE GRADE BREAK OCCURRING IN THE CROSS SECTION SHALL FALL BETWEEN DRIVING LANES.
3. STRUCTURAL SECTION SHALL BE IN ACCORDANCE WITH STANDARD SPECIFICATION SECTION 401 AND STANDARD DRAWING NOS. 200 AND 200.1.
4. THIS STANDARD IS COMPLETE STREET ALTERNATE STREET SECTION TO BE USED AT LOCATIONS DETERMINED BY EACH LOCAL JURISDICITON. NO ABOVE GROUND OBJECTS SHALL BE PLACED WITHIN THE 5 FOOT SIDEWALK.
5. UNDERGROUND DRY UTILITIES SHALL BE PLACED IN A UTILITY CORRIDOR UNDER THE SIDEWALK.

		AGENCY APPROVED							L		
SPECIFICATION REFERENCE		UNIFORM STANDARD DRAWINGS CLARK COUNTY AREA									
302	AGGREGATE BASE	SUPPLEMENTAL DRAWING									
401	BITUMINOUS PAVEMENT	MINOR COLLECTOR									
406	PRIME COAT										
407	FOG SEAL										
501	CONCRETE										
		COMPLETE STREET ALTERNATIVE									
		DATE 07-01-12	DWG. NO. 205.3.S1								

NEW DRAWING