



NOTES:

SEE DWG. 500AL SHEET 2 OF 2

SPECIFICATION REFERENCE		UNIFORM STANDARD DRAWINGS CLARK COUNTY AREA	
302	AGGREGATE BASE	0 TO 5 YEARS PAVEMENT RESTORATION LONGITUDINAL CUT	
401	BITUMINOUS PAVEMENT		
406	PRIME COAT		
407	FOG SEAL		
501	CONCRETE		
		DATE 6-12-08	DWG. NO. 500AL
		SHEET 1 OF 2	

NOTES:

1. IF THERE IS A MEDIAN, RESTORATION MAY BE LIMITED TO THE AREA BETWEEN C & G AND THE MEDIAN CURB.
2. WHEN EXISTING PAVEMENT IS 2" THICK OR LESS, PAVEMENT WITHIN THE RESTORATION AREA SHALL BE REMOVED AND REPLACED IN KIND AS REQUIRED BY THE ENTITY.
3. IF SAWCUT LINE IS WITHIN FIVE FEET OF EDGE OF EXISTING ASPHALT CONCRETE SURFACE OR EXISTING SAWCUT LINE, MILL AND OVERLAY OR REPLACE TO THAT EDGE.
4. PAVEMENT RESTORATION AREA SAWCUT LINES SHALL NOT FALL WITHIN STREET INTERSECTION.
5. IF CUT IS WITHIN A LANE , PAVEMENT RESTORATION MUST EXTEND TO THE NEXT LANE LINE.
6. THE ENTITY'S REQUIREMENTS TAKE PRECEDENCE OVER ANY MINIMUM REQUIREMENTS SHOWN HEREON.

New Drawing
Approved 06/12/08
Effective 07/01/08

SPECIFICATION REFERENCE		UNIFORM STANDARD DRAWINGS CLARK COUNTY AREA		
302	AGGREGATE BASE	0 TO 5 YEARS PAVEMENT RESTORATION LONGITUDINAL CUT		
401	BITUMINOUS PAVEMENT			
406	PRIME COAT			
407	FOG SEAL			
501	CONCRETE			
		DATE 6-12-08	DWG. NO. 500AL	SHEET 2 OF 2