







## FRONT VIEW

SIDE VIEW

## NOTES:

- 1. SIGN SHALL BE DOUBLE FACED.
- 2. SIGN PANELS SHALL BE FABRICATED OF CLEAR, IMPACT RESISTANT, ACRYLIC SHEETING WITH ALUMINUM FRAMING.
- 3. SIGN PANEL SHALL BE COVERED WITH WHITE, WIDE-ANGLE, TRANSLUCENT PRISMATIC TYPE XI REFLECTIVE SIGN FACE SHEETING, AND EITHER REVERSE-SCREENED WITH MANUFACTURER'S RECOMMENDED GREEN INK AND CLEAR COATING OR OVERLAID WITH GREEN ELECTRONIC CUTTABLE TRANSPARENT OVERLAY FILM.
- 4. SHEETING SHALL BE APPLIED IN A VERTICAL ORIENTATION IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATION.
- 5. SIGN PANEL SHALL BE CAPABLE OF WITHSTANDING WINDS OF 90 MPH OR GREATER WITHOUT DAMAGE OR SEPARATION FROM THE SIGN ENCLOSURE.
- 6. LETTERS FOR STREET NAMES SHALL BE 12" SERIES D, UNLESS OTHERWISE SPECIFIED BY THE ENGINEER, AND SHALL BE UPPER AND LOWERCASE. IF NECESSARY TO MAKE SPACING FIT, 12" SERIES C LETTERS MAY BE USED. LOWER CASE LETTERS SHALL BE 9" IN HEIGHT. LETTERS FOR CARDINAL DIRECTION, STREET NAME SUFFIX, AND BLOCK NUMBER SHALL BE 5" SERIES C, AND SHALL BE IN ALL UPPER CASE.
- 7. APPROVAL OF SHOP DRAWING OF SIGNFACE LAYOUT BY THE ENGINEER IS REQUIRED PRIOR TO FABRICATION OF SIGN PANELS.

|                         |  | AGENCY APPR                                    | OVED    | В | С      | Η | L     | М    |   |
|-------------------------|--|--|---------|---|--------|---|-------|------|---|
| SPECIFICATION REFERENCE |  | UNIFORM STANDARD DRAWINGS<br>CLARK COUNTY AREA |         |   |        |   |       |      |   |
|                         |  | SUPPLEMENTAL DRAWING                           |         |   |        |   |       |      |   |
|                         |  | ILLUMINATED STREET NAME SIGN<br>- SIGN PANEL   |         |   |        |   |       |      |   |
|                         |  | DATE: 01-01-13                                 | DWG. NO |   | 818.S1 |   | SHEET | 4 OF | 5 |

